

TWINAIR 2800+

Oil injected - Diesel driven HP compressor



Performance data for information only

General information

Dimensions (l x b x h)	mm	6058x2438x2890	Sound power level (LWA)	dB(A)	115
Weight with full fuel tank	kg	18.000	Sound pressure at 7 meter (LPA)	dB(A)	87
Capacity of fuel tanks	l	1800			

Compressor information

Number of compression stages		2
Air outlet connection	BSP	2 x 3"
After cooler	°C	A + 15
Max. working pressure	bar(e)	35
Min. effective working pressure	bar(e)	15
Free air delivery @35barg	m ³ /min	2 x 35
Free air delivery @22barg	m ³ /min	2 x 39
Fuel consumption @ 100% FAD	l/h	2 x 101
Max. ambient temperature	°C	50

Main features

Offshore & Rig Safe equipment - CE certified	PACE & XPR technology on board
Remote monitoring & screen mirroring	External emergency stop (110/24 volt)
Stacking option to create 5.600 cfm on a 20ft footprint	20 ft ISO DNV 2.7-1 container & DNV certified slings
External fuel connection inlet ¾ outlet ½ Integrated	Spillage free container
Integrated after cooler & water separator	Option to comply with NORSOK Z-015 standards



Atlas Copco Rental

www.atlascopcorental.com

Subject to change without prior notice. Information is for guidance only. Please contact your nearest Rental office for detailed application advice.