

**COMPRESSOR DATA SHEET**

**Federal Uniform Test Method for Certain Air Compressors Not Applicable**

**Rotary Compressor: Variable Frequency Drive**

**MODEL DATA - FOR COMPRESSED AIR**

1	Manufacturer: Atlas Copco														
2	Model Number: ZT 160 VSD+-10.4	Date: 01-06-2024													
	<input checked="" type="checkbox"/> Air-cooled <input type="checkbox"/> Water-cooled	Type: Screw													
	<input type="checkbox"/> Lubricated <input checked="" type="checkbox"/> Oil-free	# of Stages: 2													
3	Full Load Operating Pressure*(b)	150.0	psig*(b)												
4	Drive Motor Nominal Rating	107.3 & 107.3	hp												
5	Drive Motor Nominal Efficiency	97.0 & 97.0	percent												
6	Fan Motor Nominal Rating (if applicable)	11.8	hp												
7	Fan Motor Nominal Efficiency	69.9	percent												
8*	Input Power (kW)	Capacity (acfm) *(a,d)	Specific Power (kW/100 acfm)*(d)												
	176.3      Max	830.5	21.2												
	138.4	663.3	20.9												
	105.5	496.0	21.3												
	75.5	328.8	23.0												
	45.8      Min	161.5	28.3												
9*	Total Package Input Power at Zero Flow*(c,d)	0.0	kW												
10	<table border="1"> <caption>Graph Data Points</caption> <thead> <tr> <th>Capacity (ACFM)</th> <th>Specific Power (kW/100ACFM)</th> </tr> </thead> <tbody> <tr> <td>150</td> <td>28.5</td> </tr> <tr> <td>330</td> <td>23.0</td> </tr> <tr> <td>496</td> <td>21.3</td> </tr> <tr> <td>663</td> <td>20.9</td> </tr> <tr> <td>830</td> <td>21.2</td> </tr> </tbody> </table>			Capacity (ACFM)	Specific Power (kW/100ACFM)	150	28.5	330	23.0	496	21.3	663	20.9	830	21.2
Capacity (ACFM)	Specific Power (kW/100ACFM)														
150	28.5														
330	23.0														
496	21.3														
663	20.9														
830	21.2														

\*For models that are tested in the CAGI Performance Verification Program, these items are verified by program administrator

Consult CAGI website for a list of participants in the third party verification program:

[www.cagi.org](http://www.cagi.org)

Notes:

- Measured at the discharge terminal point of the compressor package in accordance with ISO 1217, Annex E; acfm is actual cubic feet per minute at inlet conditions.
- The operating pressure at which the Capacity and Electrical Consumption were measured for this data sheet.
- No Load Power. In accordance with ISO 1217, Annex E, if measurement of no load power equals less than 1%, manufacturer may state "not significant" or "0" on the test report.
- Tolerance is specified in ISO 1217, Annex E, as shown in table below:  
NOTE: The terms "power" and "energy" are synonymous for purposes of this document.

Member



Volume Flow Rate at specified conditions		Volume Flow Rate	Specific Energy Consumption	No Load / Zero Flow Power
m <sup>3</sup> / min	ft <sup>3</sup> / min	%	%	
Below 0.5	Below 15	+/- 7	+/- 8	+/- 10
0.5 to 1.5	15 to 50	+/- 6	+/- 7	
1.5 to 15	50 to 500	+/- 5	+/- 6	
Above 15	Above 500	+/- 4	+/- 5	