



Industrial



1-1/2" Super Industrial Impact Wrench



- Best Power-to-Weight ratio
- Premium quality
- Ergonomically designed



People. Passion. Performance.

CP6135-D80 1-1/2" Super Industrial Impact Wrench



Power & Durability



BEST POWER-TO-WEIGHT RATIO IN ITS CLASS 167.1 ft-lbs./lb. – 500 Nm/kg



MONSTER POWER

- 5,900 ft-lbs. 8000Nm of max. torque
- 760 powerful BPM



HIGH DURABILITY Grease encapsulated Rocking Dog clutch provides continual lubrication for increased durability



RELIABLE STEEL MOTOR

Long lasting motor constructed with premium-quality steel parts



ROUGH USE Rugged high-quality steel clutch housing ideal for harsh conditions



ALUMINUM BODY Robust, lightweight and finished motor housing



Applications



Oil, Gas and Petrochemical



Mining and Minerals Processing



Metal Transformation



Manufacturing







INTEGRATED OILER

Oil spray lubrication increases tool performance and lifetime

Ergonomically Designed for Maximum Safety

LOW VIBRATION 10.9 m/s² vibration only (k=6.3)

LOW NOISE 99 dB(A) sound pressure

HOLE RETAINER

retainer ring

Provides positive socket

retention when used with

BALANCER ATTACHMENT Includes suspension hook for increased operator productivity and ease of use

REVERSIBLE TRIGGER

- Flexible design allows for either inside or outside trigger placement
- Parts and instructions included



45° angled down exhaust to blow air away from work area.



ERGONOMIC HANDLING Low vibration.

6-position handle for optimal comfort and flexibility



 Designed for easy operation with gloves
Direction indicator molded into tool housing



INCREASED CONTROL Full teasing steel trigger for smooth operation and durability

Model		Part # So		quare Drive		Impact Mechanism		Socket Retainer		ner Bolt (Bolt Capacity (ISO) 10.9	
CP6135-D80 615 159		380	1-1⁄2"		Rocking Dog		Hole			Up to M48 / 2"		
Free Speed	Blows / Minute	Working	g Torque	Max T	orque	We	ight		ons.@ ad	Sound Pressure	Sound Power	Vibration
RPM	BPM	ft-lbs.	Nm	ft-lbs.	Nm	lbs.	kg	cfm	l/s	dB(A)	dB(A)	m/s²(k)
2,900	760	740 - 4,055	1,000 - 5,500	5,900	8,000	35.3	16	84.5	40	99	110	10.9 (6.3)

Hose int. 5/8" (16mm)- @ 90 PSI (@6.3 Bar) See dimensions on the next page. Listed specifications are for reference only. Please check tool documentation.












Over 110 years of experience

Since 1901 the Chicago Pneumatic (CP) name has represented reliability and attention to customer needs, with construction, maintenance and production tools and compressors designed for specific industrial applications. Today, CP has a global reach, with local distributors around the world.

Our people start every single day with a passion to research, develop, manufacture and deliver new products that are meant to meet your needs not only today, but tomorrow as well.

To learn more about our extensive range of tools, construction equipment, industrial and portable compressors, accessories and workshop equipment, please visit www.cp.com.

DIMENSIONS



C C D in. mm in. mm 5.3 135 9.4 239

Size Max. Flow Rate Part # NPT Part # BSP Туре l/sec in 894 016 8517 894 016 8480 1/2 2 stage 110 50 894 016 8518 894 016 8481 1/2 110 50 3 stage 3/4 894 016 8519 894 016 8483 2 stage 220 100 894 016 8520 894 016 8484 3/4 3 stage 220 100 FRL Stand Part # Description 615 812 0450 FRL stand for 2 stage 1/2" metallic FRL (frame only)

FRL units will improve the productivity and lifetime of your pneumatic tools.

ACCESSORIES SELECTION

FILTER-REGULATOR-LUBRICATOR



AIR FLEX

TUNE-UP KIT					
I	Model	TUNE-UP KIT			

BALANCERS

CP AIR FLEX

Part # NPT

894 017 1567

Model	Part #	Load Range		Str	oke	Net Weight	
Model	Fait #	lb.	kg	ft	m	lb.	kg
CP9958	894 109 9580	39.7-48.5	18-22	6.5	2,000	13.2	6.0
CP9959	894 109 9590	48.5-55	22-25	6.5	2,000	14.6	6.6

Size

1/2



IN LINE OILERS

CP6135-D80



Chicago Pneumatic



615 398 2790

GLOVES

Part #	Description
894 017 1574	Impact glove size medium
894 015 8618	Impact glove size large
894 015 8619	Impact glove size X-large
894 017 1573	Impact glove size XX-large

Part # BSP

894 017 1566

SOCKETS

SCAN THE QR CODE TO GO TO THE SOCKETS CATALOG (1¹/₂" ARE METRIC ONLY)

Max. Flow

cfm

74

l/sec

35

All sockets sizes and types available on www.cp.com



www.cp.com

English © Copyright 2014